

DATE

STANDARDS

DESIGNED IN ACCORDANCE WITH, AND FABRICATION TO MEET THE FOLLOWING STANDARDS:

- 1. AS1428.4.1:2009, TACTILE GROUND SURFACE INDICATORS FOR THE ORIENTATION OF PEOPLE WITH VISION IMPAIRMENT.
- 2. AS1627.4 METAL FINISHING -PREPARATION AND PRE-TREATMENT OF SURFACES - ABRASIVE BLAST CLEANING OF STEEL.
- 3. AS2312:2002/AMDT 1:2004, GUIDE TO PROTECTION OF IRON AND STEEL AGAINST EXTERIOR ATMOSPHERIC CORROSION, 1994.
- 4. GUIDE TO ENGINEERING PRACTICE, 'PEDESTRIANS', PART 13, AUSTROADS.
- 5. AUSTRALIAN ROAD RULES, 1999, WWW.NRTC.GOV.AU
- 6. AS4506 -2005, METAL FINISHING-THERMOSET POWDER COATINGS.
- 7. AS4680:2006, HOT DIP GALVANISING.

NOTES

- WELDING TO BE ACCORDANCE TO AS1554.1 CAT 1 GP WELDING, ALL SHARP EDGES & BURRS REMOVED.
- 2. PART SHOULD BE SUPPLIED CLEAN AND FREE FROM MARKS, BURRS, SCUFFS, DISTORTION AND WARPAGE.
- 3. ENSURE ANTI-SEIZE IS ON ALL NUTS AND BOLTS PRIOR TO ASSEMBLY.
- 4. DRAWING TO AS1100 DRAWING STANDARDS.
- 316 S.S AND 316 S.S FASTENERS TO BE USED 5. THROUGHOUT FOR COASTAL INSTALLATIONS OR ANY ENVIRONMENT WITH HIGH CORROSION.
- 6. ALL TOLERANCES ± 0.5mm UNLESS OTHERWISE SPECIFIED.

MATERIAL

- MATERIAL: 316 STAINLESS STEEL 1.
- 2. COLOUR: NATURAL
- 3. FINISH: DEBURRED

STRUCTURAL DESIGN REVIEWED AND CERTIFIED FOR ISSUE			
NAME: <u>B.C. PLANT</u>	RPEQ:88 <u>07</u>		
SIGNATURE: <u>ON ORIGINAL</u>	DATE: 10/ 05/ 18		

BRISBANE CITY COUNCIL STANDARD DRAWING

G FOUNTAIN . VALVEMOUNT	scale 1:2	
	DWG NO. BSD-7331	
Г 27 OF 27		
	AD	A