

ITEM	DESCRIPTION	REFERENCE	APPROVED PRODUCT REFERENCE
1	ROAD LIGHT LUMINAIRE	RATE 2 ENERGEX CONTRACT (SYLVANNIA ROADSTAR)	
		REFER TO APPROVED STREET LIGHT DESIGN	
		S150	5475
		S250	5460
2	ROAD LIGHTING POLE OUTREACH ARM	RATE 2 ENERGEX CONTRACT (NB OUTREACHES HAVE 2.0m UPLIFT TO GAIN MOUNTING HT.)	
		1.5m	5734
		3.0m	5750
		4.5m	5757
3	LUMINAIRE TRANSITION PIECE	BCC STORES	
		a) 9.0m MOUNTING HEIGHT (1400mm)	
		b) 10.5m MOUNTING HEIGHT (2900mm)	
		c) 12.0m MOUNTING HEIGHT (4400mm)	
4	TRAFFIC SIGNAL MAST ARM	BCC STORES	The second second
		2.5m	
		5.0m	
T see to		8.5m	
5	TRAFFIC SIGNAL JUNCTION BOX	BSD-4102	
		29 CORE	
		36 CORE	
1,	a though the open and a fine and a fine	51 CORE	
6	FOOTING	PILE DEPTH: BSD-4154	
7	ANCHOR CAGE	BSD-4154	
8	ELECTRICAL CABLE JOINTING PIT & LID	TMR DWG 1415, BSD-4032 & BSD-4033	
9	100 uPVC LD U/G CONDUIT		
10	PEDESTRIAN PUSH BUTTON UNIT a) PEDESTRIAN PUSH BUTTON UNIT		
	b) 4-7/0.50 CABLES	FROM PUSH BUTTON TO FINIAL (REQUIRED FOR STANDARD PUSH BUTTONS)	
	c) FIGURE 8 CABLE	FROM PUSH BUTTON TO FINIAL (SUPPLIED WITH AUDIO—TACTILE PUSH BUTTONS)	
	d) ADHESIVE LABEL "CROSS WITH CARE"		
11	TARGET BOARD	a) SINGLE b) DOUBLE	
11	STRAPS	a) 260mm (PROVIDED WITH 300mm & PEDESTRIAN LANTERNS)	
12	STRAPS	b) 150mm (PROVIDED WITH 300mm & PEDESTRIAN LANTERNS)	
		STRAPS OTHER THAN THOSE PROVIDED MAY BE USED AS REQUIRED.	
1.7	LIADDIANDE FIVING CODEMS & DOLTS	STRAPS WITHER THAN THUSE PROVIDED MAY BE USED AS REQUIRED.	
13	HARDWARE FIXING SCREWS & BOLIS	a) 4/M8 x 20mm ZINC PLATED PHILLIPS CHEESE HEAD SCREWS (WITH WASHERS) FIXING LIGHTING JUNCTION BOX TO POST. b) 2/M12 x 50mm GALVANISED BOLTS (WITH NUTS & WASHERS) FIXING LANTERN STRAPS TO POST LANTERN FIXING LUGS AND OVERHEAD LANTERN FIXING DISCS. c) 2/M8 x 25mm PLATED SET SCREWS FIXING PUSH BUTTON UNIT TO POST. d) 1/M12 x 50mm GALVANISED BOLT FIXING AUDIO—TACTILE DRIVER UNIT TO POST.	

# GENERAL NOTES

- 1. 25mm MAX. HEIGHT OF THREAD TO BE LEFT PROTRUDING ABOVE BASE PLATE LOCK DOWN NUT.
- 2. MIX SAND/CEMENT GROUT IN A 3:1 RATIO BY VOLUME. ADD ENOUGH WATER TO GIVE A WORKABLE MIX. PACK THE MIX BENEATH THE BASE PLATE AND CHAMFER SIDES TO GROUND AT 45°.

### ASSOCIATED DOCUMENTS

- 1. ENERGEX PUBLIC LIGHTING MANUAL (CONSTRUCTION)
- 2. ENERGEX PUBLIC LIGHTING MANUAL (POLICY)
- 3. ENERGEX APPROVED PRODUCTS LIST (FORM 2020)
- 4. AS2979 TRAFFIC SIGNAL MAST ARM
- 5. AS3000 SAA WIRING RULES

# REFERENCED DOCUMENTS

#### STANDARD DRAWINGS:

- 1. BSD-4001: 'ELECTRICAL CABLE DESIGN CLEARANCES'.
- 2. BSD-4003: 'TRAFFIC SIGNAL/LIGHTING POLE ELECTRICITY SUPPLY WARNING LABELS'.
- 3. BSD-4032: 'CIRCULAR CABLE JOINTING PIT 600mm DIAMETER COLLAR'.
- 4. BSD-4033: 'CIRCULAR CABLE JOINTING PIT 600mm DIAMETER COVER'.
- 5. BSD-4102: 'TRAFFIC SIGNAL JUNCTION BOX'.
- 6. BSD-4124: 'MAST ARM DETAILS 2.5 & 5M OUTREACH'.
- 7. BSD-4154: 'RAGBOLT ASSEMBLIES MAST ARM 2.5 & 5M OUTREACH'.
- 8. TMR DWG. 1415: 'TRAFFIC SIGNALS/ROAD LIGHTING CIRCULAR CABLE JOINING PIT 600 DIAMETER'.

				4,100	ı
				1.1	١.
С	GROUTING DIMENSION ALTERED, ADDED ADDITIONAL BSD PLAN REFERENCES	B.W.5/9/16	AMC 9/16	AH6 5 916	M
В	ITEM 12 CHANGED	BW 3.03.15	AMG 3.03.15	AMG 3.03.15	Г
· A	Drawing Converted from UMS Series April 2014	APR '14	APR '14	APR '14	
ISSUE	AMENDMENT	DRAWN DATE	CHK'D DATE	APPR'D DATE	1

	DRAWING AUTHORISED FOR PUBLICATION B. BALL SIGNATURE ON ORIGINAL	DESIGN	Std Dwgs WG	DATE	April '01	Γ
,	DATED 29/6/01	DRAWN	CPO - P&D	DATE	April '01	
6	MANAGER ASSET SUPPORT - R.P.E.Q: 3 8 5 2  DESIGN APPROVED	CHECKED	R. WILSON	DATE	May'01	1
	K. MEMORY SIGNATURE ON ORIGINAL DATED 27/6/01	DRAWING FILENAME	BSD-4126.dwg	- <u> </u>		1
	SENIOR PROGRAM OFFICER NETWORK OPERATIONS - R.P.E.Q: 4 7 6 1	ASSOCIÁTED PLANS	SUPERSEDES UMS-600-055			1



## **BRISBANE CITY COUNCIL STANDARD DRAWING**

JOINT USE TRAFFIC SIGNAL MAST ARM 2.5 & 5.0m OUTREACH (RATE 2)

	ND D	1	WAATIA	J
SCALE	NOT	TO	SCALE	
BSD-4126				
ORIGINAL SIZE			REVISION	
	A3		$\subset$	