



PLAYGROUND SOFTFALL – SECTION

### GENERAL NOTES

- ENSURE MOWN HEIGHT OF GRASS (TURF) AREAS FINISHES FLUSH WITH EDGE.
- ENSURE GARDEN AREAS (MULCH) FINISH 25mm BELOW ADJACENT F.S.L.'s OF EDGE.
- ENSURE EVEN GRADE FALLS MIN. 1:50 TO RUBBER SAFETY SURFACE. F.S.L.'s OF RUBBER SAFETY SURFACE TO FINISH FLUSH WITH SOFTFALL.
- ENSURE PLAYGROUNDS ARE LOCATED IN ACCORDANCE WITH AUSTRALIAN STANDARDS, DETAILED LANDSCAPE PLAN, AND SUBDIVISION AND DEVELOPMENT GUIDELINES.
- ENSURE PARK ELEMENTS ARE CLEANED OF CONCRETE SLURRY OR SPRAY WHEN INSTALLED TO PREVENT STAINING OR DAMAGE TO APPLIED FINISHES.
- COLOUR SELECTION FOR RUBBER SAFETY SURFACES AS SPECIFIED.
- ALL DIMENSIONS IN MILLIMETRES (U.N.O.).

### CONCRETE WORKS

- ALL CONCRETE TO BE MINIMUM GRADE N25.
- ALL MACHINE PLACED (EXTRUDED) CONCRETE TO BE GRADE S32. INSTALL CONTRACTION JOINTS AT 4m INTERVALS BY FORMING GROOVES 40mm DEEP BY 6mm WIDE TO ALL EXPOSED SURFACES NORMAL TO THE ALIGNMENT OF THE KERB.

					DRAWING AUTHORISED FOR PUBLICATION PAUL COTTON SIGNATURE ON ORIGINAL DATED 03/09/04				DESIGN	Std Dwgs WG	DATE	OCT '13	BRISBANE CITY COUNCIL STANDARD DRAWING	
					MANAGER INFRASTRUCTURE MANAGEMENT R.P.E.Q.: 2546				DRAWN	CPO - P&D	DATE	OCT '13		
					DESIGN APPROVED LAUREN TEMPLEMAN SIGNATURE ON ORIGINAL DATED 31/08/04				CHECKED	UMD - E&P & IMB	DATE	OCT '13	PLAYGROUND UNDERSURFACING	
					PRINCIPAL PROGRAM OFFICER PARKS				DRAWING FILENAME	BSD-10420 (B) Playground undersurfacing.dwg				
B	Drawing Title Amended	FEB '16	JUL '16	JUL '16					ASSOCIATED PLANS	SUPERSEDES UMS-755			ORIGINAL SIZE	A3
A	Drawing Converted from UMS Series April 2014	APR '14	APR '14	APR '14									REVISION	B
ISSUE	AMENDMENT	DRAWN DATE	CHK'D DATE	APPR'D DATE										

